

# CRINT-C131R/UC220-240V

1 pole | Changeover contact



## Main circuit

Available contact materials	AgSnO <sub>2</sub>
Recommended minimum contact load	100 mA / 12 V
Maximum contact load AC	6 A / 250 V AC-1
Maximum contact load DC	6 A / 30 V DC-1
Inrush current	15 A, 2.5 ms
Rated load AC	1 500 VA
Rated load DC	fig. 3.
Rated current	6 A
Mechanical endurance (cycles)	≥ 1 000 000
Electrical endurance at rated load AC-1 (cycles)	≥ 10 000

## Control circuit

Nominal voltage	see table product references
Operating voltage range	0.7 U <sub>N</sub> ... 1.25 U <sub>N</sub>
Pick-up voltage	≥ 0.7 U <sub>N</sub>
Release voltage	≤ 0.1 U <sub>N</sub>
Power consumption AC / DC	0.9 VA / 0.4 W
Frequency range	0; 50 ... 60 Hz

## Insulation

Test voltage open contact	1 kV / 1 min
Test voltage contact / coil	4 kV / 1 min
Overvoltage category	III
Pollution degree	3

## General data

Storage temperature (no ice)	-40 ... 85 °C
Operation temperature	-40 ... 70 °C (-40 ... 55 °C for control voltage > 60 V)
Relative humidity, no condensation	5% to 85% RH
Pick-up time / bounce time	7 ms / ≤ 8 ms
Release time / bounce time	15 ms / ≤ 4 ms
Conductor cross section control / main circuit	Push-in terminal
- Single wire	0.34 mm <sup>2</sup> / AWG 22 ... 2.5 mm <sup>2</sup> / AWG 14
- Multi wire (un-crimped)	0.34 mm <sup>2</sup> / AWG 22 ... 2.5 mm <sup>2</sup> / AWG 14
- Multi wire (crimped)	0.34 mm <sup>2</sup> / AWG 22 ... 1.5 mm <sup>2</sup> / AWG 16
Ingress Protection	IP 20
Mounting	TH35 (EN 60715)
Mounting position	any
Weight	30 g
Housing material	PA

## Product references

Description	Type	220-240
Push-in	CRINT-C131R/UC...V	✓

«...» List control voltage to complete product references

## Accessories

Potential bridge bar	CRINT-BR20-BU (BAG 5 PCS), CRINT-BR20-BK (BAG 5 PCS), CRINT-BR20-RD (BAG 5 PCS)
Label plate	CRINT-LAB (BAG 4X16 PCS)
Marking strip	BS11-PI (50m tape)

## Replacement relays

Description	Type	60
DC	CRINT-R11/DC...V	✓

«...» List control voltage to complete product references

60 V relay used for all sockets with a minimum nominal voltage higher or equal 60 V




fig. 1. Wiring diagram




fig. 2. AC voltage endurance




fig. 3. DC load limit curve





fig. 4. Dimensions (mm)



## Technical approvals, conformities

Standards EN 60664-1; IEC/EN 61810-1

Railway EN 45545-2; EN 50155

Approvals