

# RIC32-400/UC24V

2 or 4 pole | 32 A | 7 kW



## Main circuit

Available contact materials	⚡ AgNi
Rated voltage	400 V AC
Rated current AC-1	32 A
Recommended minimum contact load	50 mA, 17 V
Inrush current	60 A, 100 ms
Rated load AC-1	7 kW
Rated load AC-3	1.3 kW
Rated load DC-1	see fig. 2
Mechanical endurance (cycles)	≥ 10 000 000
Electrical endurance at rated load AC-1 (cycles)	≥ 200 000
Electrical endurance at rated load AC-3 (cycles)	≥ 500 000
Electrical endurance at rated load DC-1 (cycles)	≥ 100 000
Switching frequency at rated load AC-1 (cycles / h)	≤ 600
Switching frequency at rated load AC-3 (cycles / h)	≤ 600
Switching frequency at rated load DC-1 (cycles / h)	≤ 300

## Control circuit

Nominal voltage	see table product references
Operating voltage range	0.85 ... 1.1 U <sub>N</sub>
Pick-up voltage	≤ 0.85 U <sub>N</sub>
Release voltage	≥ 0.1 U <sub>N</sub>
Pick-up time	15 ... 45 ms
Release time	20 ... 70 ms
Power consumption AC / DC	2.6 VA / 2.6 W
Frequency range	40 ... 500 Hz

## Insulation

Rated insulation voltage	440 V
Rated impulse withstand voltage open contact	4 kV / 1 min
Pollution degree	3
Overvoltage category	III
Clearance of open contact	3.6 mm

## Wiring

Contact type control / main circuit	Screw connection, M3 / M3.5
Conductor cross section control / main circuit	2.5 mm <sup>2</sup> / 6 mm <sup>2</sup>
Stripping Length control / main circuit	7 mm / 9 mm
Nominal screw torque control / main circuit	0.6 Nm / 1.2 Nm
Screwdrive control / main circuit	PZ1 / PZ1
Max. wire count control / main circuit	1
Dual sleeve control / main circuit	1

## Housing and environmental conditions

Storage temperature (no ice)	-30 ... 80 °C
Ambient temperature operation 2 devices, 1 spacer	40 ... 55 °C
Ambient temperature operation 3 devices, 1 spacer	-15 ... 40 °C
Relative humidity, no condensation	95 %
Ingress Protection	IP 20
Weight	140 g (2 pole) / 250 g (4 pole)
Color	Black
Housing material	PA 6
Operation Altitude	Max. 2 000 m
Mounting	DIN rail
Dimensions	see fig. 3
Mounting position	see installation instructions




fig. 1. Wiring diagram




fig. 2. DC load limit curve





fig. 3. Dimensions (mm)



## Technical approvals, conformities

Standards IEC/EN 60947; IEC/EN 61095

Approvals

# RIC32-400/UC24V

2 or 4 pole | 32 A | 7 kW



## Safety

MTTF - Mean time to failure, AC-1 (h)	3,750
MTTF = $1/\lambda = B10/(0.1 n_{op})$ , AC-3 (h)	7,500
MTTF <sub>d</sub> - Mean time to failure dangerous, AC-1 (h)	5,000
MTTF <sub>d</sub> = $1/\lambda = B10_d/(0.1 n_{op})$	10,000
B10 - Number of operating cycles until 10 % of devices fail, AC-1	112,500
B10 - Number of operating cycles until 10 % of devices fail, AC-3	225,000
B10 <sub>d</sub> - Number of operating cycles until 10 % of devices fail, AC-1	150,000
B10 <sub>d</sub> = B10/ratio of dangerous failures, AC-3	300,000
$\lambda$ - Failure rate, AC-1 (1/h)	0.000266
$\lambda = (0.1 n_{op})/B10$ , AC-3 (1/h)	0.000133
$\lambda_d$ - Failure rate dangerous, AC-1 (1/h)	0.0002
$\lambda_d = (0.1 n_{op})/B10_{op}$ , AC-3 (1/h)	0.0001
Ratio of dangerous failures (%)	75
$n_{op}$ - Operating cycles (operating cycles/h)	300

## Accessories

Sealing cover	RIC-SEAL25
Spacer	RIC-DIST
Busbar	RIC-PS-2-3, RIC-PS-2-4, RIC-NS-2-1
End covers	RIC-EK-23 (BAG 10 PCS), RIC-EK-40 (BAG 10 PCS)
Auxiliary contact	RIC-AUX02, RIC-AUX11, RIC-AUX20




fig. 1. Wiring diagram




fig. 2. DC load limit curve





fig. 3. Dimensions (mm)



## Technical approvals, conformities

Standards IEC/EN 60947; IEC/EN 61095

Approvals